

STRAIGHT, LEVEL, UNLIGHTED HIGHWAY UNDER NORMAL ATMOSPHERIC CONDITIONS, UNLESS A DIFFERENT TIME OR CONDITION IS EXPRESSLY STATED.

(B) WHENEVER A REQUIREMENT IS DECLARED IN THIS SUBTITLE AS TO THE MOUNTED HEIGHT OF LAMPS OR DEVICES, IT MEANS FROM THE CENTER OF THE LAMP OR DEVICE TO THE LEVEL GROUND ON WHICH THE VEHICLE STANDS WHEN THE VEHICLE IS WITHOUT A LOAD.

REVISOR'S NOTE: This section presently appears as Art. 66 1/2, §12-202.

Except for minimal changes in style and nomenclature, this section has not been revised; see General Revisor's Note to this title.

22-203. HEAD LAMPS ON MOTOR VEHICLES.

(A) EVERY MOTOR VEHICLE, OTHER THAN A MOTORCYCLE, SHALL BE EQUIPPED WITH AT LEAST TWO HEAD LAMPS WITH AT LEAST ONE ON EACH SIDE OF THE FRONT OF THE MOTOR VEHICLE, WHICH HEAD LAMPS SHALL EMIT WHITE LIGHT AND COMPLY WITH THE REQUIREMENTS AND LIMITATIONS SET FORTH IN THIS TITLE.

(B) EVERY MOTORCYCLE SHALL BE EQUIPPED WITH AT LEAST ONE AND NOT MORE THAN TWO HEAD LAMPS THAT COMPLY WITH THE REQUIREMENTS AND LIMITATIONS OF THIS TITLE.

(C) EVERY HEAD LAMP ON EVERY MOTOR VEHICLE, INCLUDING EVERY MOTORCYCLE, SHALL BE LOCATED AT A HEIGHT OF NOT MORE THAN 54 INCHES NOR LESS THAN 24 INCHES.

REVISOR'S NOTE: This section presently appears as Art. 66 1/2, §12-203.

Except for minimal changes in style and nomenclature, this section has not been revised; see General Revisor's Note to this title.

22-204. TAIL LAMPS; ILLUMINATION OF REAR REGISTRATION PLATE.

(A) (1) AFTER JUNE 1, 1971, EVERY MOTOR VEHICLE, TRAILER, SEMITRAILER, AND POLE TRAILER, AND ANY OTHER VEHICLE THAT IS BEING DRAWN AT THE END OF A COMBINATION OF VEHICLES, SHALL BE EQUIPPED WITH AT LEAST TWO TAIL LAMPS MOUNTED ON THE REAR, WHICH, WHEN LIGHTED AS REQUIRED IN §22-201.1 OF THIS SUBTITLE, SHALL EMIT A RED LIGHT PLAINLY VISIBLE FROM A DISTANCE OF 1,000 FEET TO THE REAR, EXCEPT THAT:

(I) MOTOR VEHICLES MANUFACTURED OR ASSEMBLED BEFORE THAT DATE, AND ALL MOTORCYCLES, SHALL HAVE AT LEAST ONE TAIL LAMP; AND